



## easy CRP

## wrCRP

## wrCRP+Hb

## CRP

## CRP+Hb

## Strep A

## iFOBT

Sample type	Whole blood, serum, plasma	Whole blood, serum, plasma	Whole blood, serum, plasma	Whole blood, serum, plasma	Whole blood, serum, plasma	Throat sample	Faeces
Sampling	One-step Sample Collector	Orange striped capillary	Orange striped capillary	Blue striped capillary	Blue striped capillary	Throat swab	Sampling vial
Sample volume	10 µl	10 µl	10 µl	20 µl	20 µl	NA	10 mg
Sample stability in test cuvette (hours)	2	2	2	2	2	4	2
Measurement results within (min)	2	2	2	2	2	4, strong positives 2	3
Measuring range	1–200 mg/l	0.5–200 mg/l	CRP 0.5–200 mg/l Hb 50–220 g/l	5–200 mg/l	CRP 5–200 mg/l Hb 50–245 g/l	Positive/negative	10–200 µg/g (50–1000 ng/ml)
Unique combination: 1 analysis – 2 results	–	–	yes	–	yes	–	–
Number of tests	50	50	50	50	50	50	50
Storage	2–25°C	2–25°C	2–25°C	2–25°C 4 weeks 2–8°C	2–25°C 4 weeks 2–8°C	2–25°C	2–25°C 4 weeks 2–8°C
Software version	7.6.2 or newer	7.5.1 or newer	7.5.1 or newer	All versions	4.1 or newer	4.1 or newer	6.5.1 or newer
QuikRead go Instrument connectivity to HIS and LIS systems	yes	yes	yes	yes	yes	yes	yes

Email for orders: [orders@aidian.eu](mailto:orders@aidian.eu)

[www.aidian.eu](http://www.aidian.eu) / [www.quikread.com](http://www.quikread.com) / [www.tacklearm.com](http://www.tacklearm.com)



## QuikRead go Instrument

<b>Method</b>	Immunoturbidimetric and photometric
<b>Dimensions</b>	27 cm (l) x 15.5 cm (w) x 14.5 cm (h)
<b>Weight</b>	1.7 kg without power supply
<b>Storage and transportation</b>	Between 2 °C and 35 °C. Protect from rain and humidity.
<b>Country of origin</b>	Finland
<b>Power requirements</b>	100–240 V AC, 50–60 Hz power supply or accumulator unit. Power consumption 8 W.
<b>Battery use possibility</b>	Yes, supplied separately. Note that only an accumulator unit supplied for QuikRead go can be used.
<b>Memory capacity</b>	100 patient results, 100 QC results and 100 LIS offline results.
<b>Available user interface languages</b>	23
<b>Additional printer available</b>	yes
<b>Barcode reader available</b>	yes

## QuikRead go connectivity specifications

<b>Network TCP/IP communication</b>	RJ45 LAN, optional WLAN USB adapter
<b>Serial communication</b>	Through RJ45 via optional QuikRead go serial cable (RJ45 to RS-232)*
<b>Supported protocols</b>	LIS01-A2 (ASTM), POCT1-A2
<b>Communication type</b>	Unidirectional (LIS01-A2, POCT1-A2), bidirectional (POCT1-A2)
<b>USB ports</b>	3 x Type A USB port 1 x Type B USB port
<b>Sent information</b>	Patient results, QC results, result comments, notifications and error messages
<b>Result sending</b>	Automatic (LIS01-A2, POCT1-A2) or manual (LIS01-A2)
<b>Instrument software remote update</b>	yes**
<b>Remote lock/unlock</b>	yes**
<b>Remote user management</b>	yes**
<b>QC material data</b>	yes**
<b>Patient list import / positive patient identification</b>	yes**
<b>Instrument configuration</b>	yes**
<b>Instrument time setting</b>	yes**

\* LIS01-A2 only, \*\* POCT1-A2 only